



## Detoxifying Salt Contaminated Soils Using SA-1000 Oklahoma Subject Site #2

George Edwards, Edwards Environmental Corporation  
Daniel J Burdette, 3 Tier Technologies LLC

### Introduction:

Today's energy industry is dependent on the use of fracking technology for the safe and efficient exploration of high demand gas/oil. A substantial byproduct of the fracking industry is the generation of a high salt wastewater. The management and disposal of this water is a relatively safe and simple process though as with any large handling systems small spills, pipe ruptures, valve failures, and even normal site operations may lead to the inadvertent release of small quantities of this waters on the soils in or around the exploration sites.

3 Tier Technologies, using over ten years of experience solving soil challenges including high salt and bi-carbonate issues in the turf and agriculture industries, brings our proven solution to the energy industry with our latest advancement in salt management – **SA-1000**. **SA-1000** is an organic solution for salt management that uses our proprietary Polyelectrolyte Enhanced Biopolymers (PEB). PEB is the newest generation for sodium and bi-carbonate remediation for soils and wastewater.

### Objective:

3 Tier Technologies in association with Edwards Environmental Corporation, 3 Tier's distributor and technical product support in Oklahoma, identified several sites that had been impacted from frac water releases. It is common that the exploration sites are located in rural areas and that the previous land usage was for agricultural purposes. The various subject sites are agricultural sites and since the releases have exhibited loss of vegetation due to the excess sodium buildup in the relatively high clay soils. High salts will neutralize a soils ability to support vegetation of any kind though it can be safely regenerated and managed through the application of **SA-1000**. The objective of this research was to identify various sites that had been impacted by an inadvertent release of fracking wastewater and to regenerate the soils back to productive agricultural use.

Edwards Environmental Corporation identified the second subject site, a 1.74 acre tract of land which in October 2012 had a storage tank line rupture. Since the release, the site has not had any vegetation of any kind on it and it was the goal of the Energy Company and the land owner to correct the issues so that the land could be returned to a viable pasture and support various grasses for grazing.



## Methods:

Edwards Environmental Corporation initiated the salt water remediation project on Subject Site #2, a 1.74 acre tract of land, on July 24, 2013 for the first applications and August 6, 2013 for the final applications due to incorrect initial acreage information and additional product requirements.

### 1. Site Analysis:

It was determined that the principal impact of the soils was the top eight (8) inches. Initial soil samples were collected from a variety of locations within the non-vegetated area of the site. The soils collected were properly stored and delivered to Environmental Testing Inc. of Oklahoma City for analysis. The composite sample was tested for Total Soluble Salts using method SM 2520A and for Chlorides using EPA Method 300.0. Electrical Conductivity was estimated using comparative soil data from a variety of similar locations.

### 2. Site Preparation:

The subject site was well defined by the lack of any vegetation. In preparation to the corrective treatments, the area was cultivated using an agricultural disc method which loosened the soils to a depth of 4 to 6 inches. On 7/24/13 the initial discing was completed in several directions to effectively open the subject soils and insure proper penetration of the corrective treatment. After the first corrective treatment, the site received an additional cultivation to mix the material. On 8/6/13 the subject site was cultivated one additional time to prepare for the final product application. All work was completed by the Energy Companies contractor.

### 3. Treatment Process:

**SA-1000** is a liquid product that is applied by mixing with additional water to drench the soils of the subject site. The subject area had approximately 1881 cubic yards of soil to be treated. The recommended application rate for this site was 14 ounces of **SA-1000** concentrate diluted in approximately 6 gallons of water per cubic yard of soil. The site required 260 barrels of water (11,000 gallons of water). A 1000 gallon water truck was used to dilute and apply the treatment through a hose and fire nozzle. On 7/24/13 the entire site received an initial 8 ounces of **SA-1000** concentrate diluted in 6 gallons of water per cubic yard. 6000 gallons of water was applied in total. On 8/6/13, the site was tilled one more time before the final 6 ounce per cubic yard of **SA-1000** concentrate was applied. 5000 gallons of water was applied in total. After all liquid application was complete, the contractor spread 40 pounds of ryegrass and 1.5 pounds of cow peas across the site. The entire process was completed in two days.

**Note:** Due to the soil type and structure and the identified rebound effective the site exhibited, the site received an additional treatment of **SA-1000** at 8 ounce rate using the same dilutions as before. The entire site was also covered with a 4 inch layer of hay for moisture management.

### 4. Additional Sampling:

Approximately 30 and 60 days after the treatment was applied to the site, the site was sampled in fifteen different areas to make a single composite soil sample that was then delivered to Environmental Testing Inc. and tested using the same methods as previously described. The site is scheduled for additional testing in the Spring.

## Results:

The following is the specific Subject Site test data:

<b>Test</b>	<b>Pre-Treat</b>	<b>30 Day</b>	<b>60 Day</b>	<b>+/-</b>
Total Soluble Salts	15,000 ppm	3530 ppm	3990 ppm	<b>-73.4%</b>
Chlorides	6410 ppm	1170 ppm	1410 ppm	<b>-78.0%</b>
Conductivity*	36,540 um/cm	5472 um/cm	6240 um/cm	<b>-82.9%</b>

The Subject site demonstrated significant Total Soluble Salt reduction of nearly **74%**, Chloride reduction over **78%**, and Conductivity reduction of over **82.9%** in less than 60 days. It is reasonable to expect that the site will exhibit some fluctuations for the next six months depending on moisture conditions though the levels of contamination will continue to reduce over time due with normal rain and cultural practices.

**SA-1000** naturally binds the sodium molecule which eliminates the salt's ability to bind to soil particles especially clay which allows it to be safely leached and naturally filtered through the soil profile. Any salt residue that still exists in the growing profile has been detoxified so that it will not negatively affect new plants from establishing and be supported by healthy active soils. **SA-1000** safely regenerates soil affected by salts and promotes improved soil structure for healthy, productive use of the site.

The site inspection after the completion of treatments noted full germination of the applied seed and additional establishment of native grasses and weeds that had not previously been present. It was also noted that the site had additional foot traffic from the cattle since this was a pasture. The increased cattle traffic and resulting cow pies identified that new plants growing in the treated area were already being grazed by the cattle which better clarifies why a full stand of either ryegrass or cow peas never fully developed.

Both the Energy Company and landowner are very pleased with the cost effective and immediate results the treatment has provided.

## **Summary:**

**SA-1000** is a cost effective, natural solution for the management of salt in a variety of soil types. The above mentioned results are reasonable expectations on all projects though all site conditions must be considered to properly establish the best treatment solutions for each individual project. 3 Tier offers a suite of specialty remediation products which are designed to meet challenges of most contaminated sites.

The following information will be required by any 3 Tier Technical Representative to properly recommend a solution and determine the appropriate application strategy including product rates and methods of treatment:

- Type of contamination, levels of contamination, depth of contamination, how long has the site been contaminated, and how quickly does the remediation have to be completed.
- Soil type and makeup. 3 Tier recommends the soil testing regime established by Oklahoma State University for salt remediation projects.
- Regulatory standard that needs to be met if applicable
- Site accessibility for different treatment methods
- Time of year and related seasonal weather considerations
- Any previous treatments or processes done to the subject site.

For additional information on all 3 Tier Technology products or to find a local Technical Representative of our products, visit [www.3tiertech.com](http://www.3tiertech.com) or call 877-226-7498.

Edwards Environmental Corporation, contact George Edwards at [byogeorge@aol.com](mailto:byogeorge@aol.com) or call 405-850-1630.